

FEATURES

- 10000 Count digital display
- Active Backlit, Large scale display
- Volt Sense (Non Contact Voltage)
- Analog Bar graph
- True RMS reading on AC and AC+DC mode
- Torch lightening when clamed
- Auto AC/DC 1000 Amps capability and selection
- Auto AC/DC 1000 Volts capability and selection
- Auto Ohms/Continuity/Diode selection
- 100K Resistance capability
- Continuity Beeper
- Frequency Counter
- Power and Power factor measurement
- Total Harmonics distortion and Harmonics 1 to 25
- Capacitance capability
- °C / °F Temperature Function
- Inrush Current
- DCA Auto-Zeroing Key
- Peak Hold
- MIN/MAX HOLD
- Smart Data Hold
- Phase rotation indication
- Low pass Filter
- Auto Power Off
- CAT.IV 600V / CAT. III 1000V Safety Standard

**AUTOMATIC SELECTION**

Automatically detects AC, DC and AC+DC of Ampere and Voltage function with AC+DC True RMS, and automatically Selection of resistance, continuity and diode



It has active backlit display that turns ON at the touch of the button or rotate the knob, also automatically goes off to save battery life.

**INNOVATIVE LIGHTENING AND
LIVE VOLTAGE SENSING**

Torch lightening during cable clamping and automatically non contact voltage detection for better identification of working environment.

**INNOVATIVE NAVIGATOR**

Innovative Designed Navigator key optimized the function selection and feature operation with a finger of thumb.



*Technical Specifications & Appearance are subject to change without prior notice

EXTRA TEMPERATURE FEATURE

Special designed temperature test facility for daily industrial temperature measurement application.



**ADVANCED POWER FEATURES
MADE EASY**

Provides advanced Power features, Phase rotation, Total harmonics Distortion and even Harmonics 1 to 25th with easy-to-use interface, which enables fully professional power measurement application with excellent performance.



OVER-MOLDING SLIM DESIGN

Ergonomically designed comfort over-molding slim shape with extra large LCD one hand operated knob and navigator. Just fit palm of your hand and your needs.



FLEXIBLE CURRENT TEST

Integration with SFLEX-T flexible current probe expanding the current range to 3000 ACA, providing increased display flexibility making electrical measurement easier and safer



Standard Accessories

1. METRAVI 107F Power Clamp Meter
2. Flexible Clamp for 3000A Measurement
3. Test leads. set (one black, one red)
4. Temperature Probe
5. User Manual
6. Carrying case
7. Battery Installed

GENERAL SPECIFICATION

- **Display count** : 10000
- **Measuring rate** : 3 times / sec.
- **Overrange display** : "OL" or "-OL" .
- **Auto Power Off** : Approx 15 minutes.
- **Low battery indicator** : is displayed. Replace the battery when the indicator appears in the display.
- **Power requirement** : 9V battery.
- **Battery life** : ALKALINE 9V 50 hours (without Backlight).
- **Dimensions** : 87.5mm(W) x 257mm(L) x 50.5mm(D)
- **Weight** : approx. 470g (with battery)

*Technical Specifications & Appearance are subject to change without prior notice

ENVIRONMENTAL CONDITIONS

Indoor Use.

Calibration : One year calibration cycle.
 Operating temperature : 0 °C ~ 10 °C
 10 °C ~ 30 °C (≤80% RH)
 30 °C ~ 40 °C (≤75% RH)
 40 °C ~ 50 °C (≤45%RH)
 Storage temperature : -10 to 50 °C
 0 to 80% RH (batteries not fitted).
 Temperature coefficient : 0.2 x (Specified accuracy) / °C, < 18°C, > 28°C .
 Over voltage category : IEC 61010-1 600V CAT.IV. 1000V CAT.III.
 IEC 61010-2-32, IEC 61010-2-33

CAT Application field

I	The circuits not connected to mains.
II	The circuits directly connected to Low-voltage installation.
III	The building installation.
IV	The source of the Low-voltage installation.

Operating altitude : 2000m (6562 ft)
 Conductor Size : 42mm diameter
 Pollution degree : 2
 EMC : EN 61326-1
 Shock vibration : Sinusoidal vibration per MIL-T- 28800E
 (5 ~ 55 Hz, 3g maximum).
 Drop Protection : 4 feet drop to hardwood on concrete floor.

ELECTRICAL SPECIFICATIONS

Accuracy is ±(% reading + number of digits) at 23°C ± 5°C < 80%RH.

(1) Voltage

Function	Range	Accuracy
DCV	99.99V	± (0.7% + 2dgt)
	999.9V	
ACV	99.99V	± (1.0% + 5dgt)
	999.9V	50 ~ 500Hz
HFR	99.99V	50 ~ 60Hz ± (1% + 5dgt)
ACV	ACV	>60 ~ 400Hz ± (5% + 5dgt)

* DCV <1000dgt, add 6 dgt to the accuracy.
 ACV <1000dgt, add 3 dgt to the accuracy.

Overload protection : 1000Vrms
Input Impedance : 3.5MΩ // <100pF
AC Conversion Type : AC Conversions are ac-coupled, true RMS responding, calibrated to the RMS value of a sine wave input. Accuracies are given for sine wave at full scale and non-sine wave below half scale. For non-sine wave (50/60Hz) add the following Crest Factor corrections:
 For Crest Factor of 1.4 to 2.0, add 1.0% to accuracy.
 For Crest Factor of 2.0 to 2.5, add 2.5% to accuracy.
 For Crest Factor of 2.5 to 3.0, add 4.0% to accuracy.
 CF 3 @ 460V, 460A
 2 @ 690V, 690A

AC+DC Vrms Accuracy : same as ACV spec. +DCV spec.

*Technical Specifications & Appearance are subject to change without prior notice

(2) Current

Function	Range	Accuracy
DCA	99.99A	± (1.5% + 0.2A)
	999.9A*	± (1.5% + 5dgt) **
ACA	0.10A ~ 99.99A	50 ~ 60Hz ± (1.5% + 5dgt) **
	999.9A*	>60 ~ 400Hz ± (2% + 5dgt) **
HFR	99.99V	50 ~ 60Hz ± (1.5% + 5dgt) **
ACA	ACV	>60 ~ 400Hz ± (5% + 5dgt) **

** The measured value <1000dgt, add 5 dgt to the accuracy.

Overload protection : 1000Arms

Position Error : ±1% of reading.

AC Conversion Type and additional accuracy is same as AC Voltage.

AC+DC Arms Accuracy : Same as ACA spec + DCA spec.

(3) Peak Hold : Peak MAX / Peak MIN

Function	Range	Accuracy
ACV	140.0V	± (3.0% + 15dgt)
	1400V	
ACV	140.0A	± (3.0% + 15dgt)
	1400A	

Overload protection : 1000 Vrms

1000 Arms

Accuracy defined for :

Sine wave, ACV>5Vrms / ACA ≥ 5Arms, Freq.50~400Hz.

- Only suitable for the repetitive events.

(4) Frequency

Function	Range	Accuracy
Frequency	20.00 ~ 99.99Hz	± (0.5% + 3dgt)
	20.0 ~ 999.9Hz	
	0.020 ~ 9.999KHz	

Overload protection : 1000 Vrms 1000 Arms

Sensitivity :

10~100Vrms for AC 100V range

10~100Arms for AC 100A range (>400Hz Unspecified)

100~1000Vrms for AC 1000V range

100~600/1000Arms for AC 600A/1000A range

(>400Hz Unspecified)

- Reading will be 0.0 for signals below 10.0 Hz.

*Technical Specifications & Appearance are subject to change without prior notice

(5) Total Harmonic Distortion :

Function	Range	Accuracy
ACA/ACV	99.9%	± (3.0% + 10dgt)

Harmonic distortion measurement :

Harmonic order	Range	Accuracy
H01 ~ H12	99.9%	± (5% + 10dgt)
H13 ~ H25		± (10% + 10dgt)

Overload protection : 1000 Vrms 1000 Arms

- If ACV<10Vrms or ACA <10Arms, it will display "rdy".
- If the fundamental frequency out of range 45 ~ 65Hz, it will display "out.F".

(6) Inrush Current :

Function	Range	Accuracy
ACA	99.99A	± (2.5% + 0.2A)
	999.9A *	± (2.5% + 5dgt)

Overload protection : 1000 Vrms 1000 Arms

Accuracy defined for :

- Sine wave, ACA ≥10Arms, Freq. 50/60Hz
- Integration time about 100m sec

(7) Active Power : Watt (DC/AC)

Function	Range	Accuracy
ACW / DCW	9.999 kW**	A,error×V,reading+ V,error×A,reading
	99.99 kW	
	999.9kW*	

** The measured value<1.000kW, add 10 dgt to the accuracy.

Overload protection : 1000 Vrms 1000 Arms

Accuracy defined for :

ACW :

Sine wave, ACV≥10 Vrms, ACA≥ 5 Arms

Freq. 50~60Hz, PF=1.00

DCW:

DCV ≥10V, DCA ≥ 5 A

(8) Power Factor

Function	Range	Accuracy
PF	1.00	±5dgt

Overload protection : 1000 Vrms 1000 Arms

(9) Resistance & Continuity & Diode :

Function	Range	Accuracy
Resistance	999.9 Ω	± (1.0% + 5dgt)
	9.999 kΩ	± (1.0% + 3dgt)
	99.99 kΩ	
Continuity	999.9 Ω	± (1.0% + 5dgt)
Diode	0.40~ 0.80V	± 0.1V

Overload protection : 1000Vrms

Max. Test Current : Approx. 0.5mA.

Maximum Open Circuit Voltage for Ω : Approximate 3V

Maximum Open Circuit Voltage for diode : Approximate ±1.8V

Continuity Threshold : <30Ω Beep On.

> 100Ω Beep OFF.

Continuity Indicator : 2 KHz Tone Buzzer

Continuity response time : < 100ms.

*Technical Specifications & Appearance are subject to change without prior notice

(10) Capacitance :

Function	Range	Accuracy
Capacitance	3.999 µF	± (1.9% + 8dgt)
	39.99 µF	
	399.9 µF	
	3999 µF	

Overload protection : 1000 Vrms

(11) Flex AC Current (voltage input):

Function	Range(1mV/1A)	Accuracy *
ACA	300.0A/3000A	1%+5dgt (50~500Hz) **
HFR ACA	300.0A/3000A	1%+5dgt(50~60Hz) ** 5%+5dgt(61~400Hz) **
Peak	420.0A/4200A	3%+80dgt(50~500Hz)
INRUSH	300.0A/3000A	2%+10dgt(50/60Hz)
Frequency	99.99Hz/999.9Hz	0.5%+3dgt(<500Hz)
THD	99.9%	5%+10dgt
Harm H01-H12	99.9%	5%+10dgt

*The accuracy of **METRAVI sFlex-T** is not included.

**ACA <300dgt, add 3 dgt to the accuracy.

Overload protection : 1000Vrms

Trigger level of INRUSH : 1% of current range

(12) Temperature

Function	Range(1mV/1A)	Accuracy *
°C	-50 °C ~ 99.9 °C	± (1% + 2°C)
	100 °C ~ 399.9 °C	± (1% + 1°C)
	400 °C ~ 1000 °C	
°F	-58 °F ~ 211.9 °F	± (1% + 4°F)
	212.0 °F ~ 751.9 °F	± (1% + 2°F)
	752 °F ~ 1832 °F	

Overload protection :1000 Vrms