

**COMMON SPECIFICATIONS**

<b>Display</b>	6 Digit 0.5" ht 7 segment LED for DEC - 500 / 502
<b>Range</b>	1 to 999999 Counts
<b>Count Input</b>	a) Proximity Switches (PNP / NPN) b) Potential free contacts c) 5 to 30 V. DC. Voltage pulse d) 230 V.AC. Mains pulse (Optional)
<b>Counting Speed</b>	0 to 3 / 30 / 100 / 1000 / 2500 Hz (Programmable)
<b>Sensor Supply</b>	12 V.DC. 30 mA max
<b>Control Input</b>	Hold (Optional)
<b>Reset</b>	Front Reset / Remote Reset (Programmable)
<b>Memory Retention</b>	Non Volatile E <sup>2</sup> PROM upto 10 years
<b>Operating Temp</b>	0 to 55 °C
<b>Relative Humidity</b>	Below 95% RH (Non condensing)
<b>Supply</b>	90 V to 270 V. AC., 50 / 60 Hz



<b>Dimensions (H x W x D) mm</b>	48 x 96 x 120	96 x 96 x 120
<b>Panel Cutout (H x W) mm</b>	46 x 92	92 x 92

\*Technical Specifications & Appearance are subject to change without prior notice